

# WCP Series



## Wall Mount Combination Systems



Single package, wall mounted, combination AC and Pressurization systems for use in industrial and/or hazardous (classified) applications

### STANDARD FEATURES:

- \*Certified by CSA (bearing the CSA mark) for compliance to applicable codes and standards
- Spark resistant fan and blower construction
- EPA approved, HFC type, R-410a refrigerant
- Single cut-out requirement for building wall
- Supply and return air registers for ductless air handling
- Through-the-wall controls section for indoor access to operating controls
- Built-in, automatic controls and equipment to manage safe air and maintain positive pressure and purge air flow to meet NFPA 496, Type X, Y, or Z requirements for the space
- Protective coatings for prolonged life of cabinet and chassis

### OPTIONS:

- Total, nominal cooling from 1.5 to 6 tons
- Electric heat (limited by temperature code and system size)
- Single or three phase operation in 60 or 50 Hz applications
- Configurable for operation in various non-hazardous and hazardous rated locations
- Type 316, stainless steel cabinet and chassis for corrosion protection
- Corrosion resistant coatings for refrigerant coils and tubing (proven to withstand 10,000 hours of salt spray test)
- Protective, component coatings for prolonged life in corrosive environments
- Totally Enclosed, Fan-Cooled (TEFC) motors
- Advanced, chemical filtration packages
- Low/High ambient packages for operation in extreme environments

### APPLICATIONS:

- Environmental control
- Control rooms, Living quarters, plant office buildings, break rooms, and other manned applications.
- MCC, RIE, DCS, LER, power, and switchgear buildings

