

# WFX Series



## Wall Mount Fans



Wall mount fans, custom-built for use in hazardous (classified) applications

### STANDARD FEATURES:

- \*Certified by CSA (bearing the CSA mark) for compliance to applicable codes and standards
- Spark resistant construction
- Angle flashing provided for wall mounting
- Standard, protective coatings for prolonged life of cabinet and chassis
- 350, 550, or 750 CFM wall mount configurations readily available

### OPTIONS:

- Factory certified roof mount configuration
- Customizable air flows to meet customer specifications
- Configurable for operation in various non-hazardous and hazardous rated locations
- Single or three phase operation in 60 or 50 Hz applications
- Single, multi-staged or redundant operation
- Supply or exhaust configurations available
- Type 304 or 316, stainless steel cabinet and chassis for corrosion protection
- Protective, component coatings for prolonged life in corrosive environments
- Totally Enclosed, Fan-Cooled (TEFC) motor
- Low/High ambient accommodations for operation in extreme environments
- Operating switches
- Dry contacts for run status monitoring

### APPLICATIONS:

- Sewage treatment plants
- Battery rooms
- Auxiliary or emergency ventilation



SHIELD AIR SOLUTIONS, INC. • 3708 GREENHOUSE ROAD • HOUSTON, TEXAS 77084 • 281.944.4300 • WWW.SHIELDAIR.COM



\*Certification may not apply to all optional configurations. Please contact our Technical Sales department for more information.

This document was last edited on 12/03/2014

Availability and information is subject to change without notice.

Marc Climatic Controls and Birdwell are product lines of Shield Air Solutions, Inc. All rights reserved